



Watershed and Groundwater
Modeling Solutions

Setting up the GSSHA Green & Ampt Infiltration Model





Green and Ampt Parameters

Watershed and Groundwater
Modeling Solutions

- Derived from soil texture index map or combination soil texture land use index map
- Assigned with mapping table
- Initial values can be taken as average values from Rawls et al. 1983
- Calibrated values are constrained within limits from Rawls et al. 1983





GSSHA Infiltration Setup

Watershed and Groundwater
Modeling Solutions


- Generate Index Maps
 - Soil or
 - Soil and Land Use Combination
- Define mapping table properties
- Establish initial conditions
- Turn on Green & Ampt simulation
- Save and run
- Visualize the results






Watershed and Groundwater
Modeling Solutions

Generate Index Maps



Soils



Land Use





Define Mapping Table Properties

Watershed and Groundwater
Modeling Solutions

GSSHA Map Table Editor

Roughness | Interception | Retention | Evapotranspiration | **Infiltration** | Initial Moisture | Soil Erosion | Contaminants | Nutrients | Continuous Maps

Using index map: NewCombined

Generate IDs Add ID Delete ID

Infiltration											
ID	1	2	3	4	5	6	7	8	9	10	11
Description1	coarse sand...	sand ...	fine sand ...	very fine sa...	loamy coars...	loamy sand ...	loamy fine s...	loamy very fi...	sandy loams...	coarse sand...	sandy loam ...
Description2	Cropland an...	Cropland an...	Cropland an...	Residential ...	Residential ...	Deciduous ...	Deciduous ...	Transportati...	Transportati...	Mixed Urba...	...
Hydraulic conductivity (cm/hr)	23.560000	23.560000	23.560000	2.000000	2.000000	23.560000	5.980000	0.500000	0.500000	0.500000	2.180000
Capillary head (cm)	4.950000	4.950000	4.950000	4.950000	6.130000	6.130000	6.130000	6.130000	11.010000	11.010000	11.010000
Porosity (m ³ /m ³)	0.437000	0.437000	0.437000	0.100000	0.100000	0.437000	0.437000	0.100000	0.100000	0.100000	0.453000
Pore distribution index (cm/cm)	0.694000	0.694000	0.694000	0.694000	0.553000	0.553000	0.553000	0.553000	0.378000	0.378000	0.378000
Residual saturation (m ³ /m ³)	0.020000	0.020000	0.020000	0.020000	0.035000	0.035000	0.035000	0.035000	0.041000	0.041000	0.041000
Field capacity (m ³ /m ³)	0.091000	0.091000	0.091000	0.091000	0.125000	0.125000	0.125000	0.125000	0.207000	0.207000	0.207000

Help Import Table... Export Table... Job Control Done



Table of Green and Ampt Values (Rawls et al, 1983)

Watershed and Groundwater
Modeling Solutions

Loamy Sand

Water-Retention properties classified by soil texture

USDA Textural Classification	Total Porosity cm ³ /cm ³ (θ_s)	Residual water content cm ³ /cm ³ (θ_r)	Effective Porosity cm ³ /cm ³ (θ_e)	Bubbling Pressure Geometric mean, cm (pb)	Pore size distribution Arithmetic Mean (λ)	Field Capacity (Water Retained at .33kPa) cm ³ /cm ³	Wilting Point (Water Retained at - 1500 kPa) cm ³ /cm ³	Hydraulic Conductivity, cmh ⁻¹ (K_s)	ψ_f (cm)
Sand	0.437	0.02	0.417	7.26	0.694	0.091	0.033	4.95	4.95
	(0.374 - 0.500)	(0.001 - 0.039)	(0.354 - 0.480)	(136 - 38.74)	(0.298 - 1.090)	(0.018 - 0.164)	(0.007 - 0.059)		
Loamy sand	0.437	0.035	0.401	8.69	0.553	0.125	0.055	6.13	6.13
	(0.368 - 0.506)	(0.003 - 0.067)	(0.329 - 0.473)	(1.80 - 41.85)	(0.234 - 0.872)	(0.060 - 0.190)	(0.019 - 0.091)		
Sandy loam	0.453	0.041	0.412	14.66	0.378	0.207	0.095	11.01	11.01
	(0.351 - 0.555)	- 0.024 - 0.106	(0.283 - 0.541)	(3.45 - 62.24)	(0.140 - 0.616)	(0.126 - 0.288)	(0.031 - 0.159)		
Loam	0.463	0.027	0.434	11.15	0.252	0.27	0.117	8.89	8.89
	(0.375 - 0.551)	- 0.020 - 0.074	(0.334 - 0.534)	(1.63 - 76.40)	(0.086 - 0.418)	(0.195 - 0.345)	(0.069 - 0.165)		
Silt loam	0.501	0.015	0.486	20.76	0.234	0.33	0.133	16.68	16.68
	(0.420 - 0.582)	- 0.028 - 0.056	(0.394 - 0.578)	(3.58 - 120.4)	(0.105 - 0.363)	(0.258 - 0.402)	(0.078 - 0.188)		
Sandy clay loam	0.398	0.068	0.33	28.08	0.319	0.255	0.148	21.85	21.85
	(0.332 - 0.464)	- 0.001 - 0.137	(0.235 - 0.425)	(5.57 - 141.5)	(0.079 - 0.559)	(0.186 - 0.324)	(0.085 - 0.211)		
Clay loam	0.464	0.075	0.39	25.89	0.242	0.318	0.197	20.88	20.88
	(0.409 - 0.519)	- 0.024 - 0.174	(0.279 - 0.501)	(5.80 - 115.7)	(0.070 - 0.414)	(0.250 - 0.386)	(0.115 - 0.279)		
Silty clay loam	0.471	0.04	0.432	32.56	0.177	0.366	0.208	27.30	27.30
	(0.418 - 0.524)	- 0.038 - 0.116	(0.347 - 0.517)	(6.68 - 158.7)	(0.039 - 0.315)	(0.304 - 0.428)	(0.138 - 0.278)		
Sandy clay	0.43	0.109	0.321	29.17	0.223	0.339	0.239	23.90	23.90
	(0.370 - 0.490)	(0.013 - 0.205)	(0.207 - 0.435)	(4.96 - 171.6)	(0.048 - 0.398)	(0.245 - 0.433)	(0.162 - 0.316)		
Silty clay	0.479	0.056	0.423	34.19	0.15	0.387	0.25	29.22	29.22
	(0.425 - 0.533)	- 0.024 - 0.136	(0.334 - 0.512)	(7.04 - 166.2)	(0.040 - 0.260)	(0.332 - 0.442)	(0.193 - 0.307)		
Clay	0.475	0.09	0.385	37.3	0.165	0.396	0.272	31.63	31.63
	(0.427 - 0.523)	- 0.015 - 0.195	(0.269 - 0.501)	(7.43 - 187.2)	(0.037 - 0.293)	(0.326 - 0.466)	(0.208 - 0.336)		

First Line is the mean value, second line is \pm one standard deviation about the mean





Establish Initial Conditions

GSSHA Map Table Editor

Soil Erosion Contaminants Nutrients Continuous Maps
Roughness Interception Retention Evapotranspiration Infiltration **Initial Moisture**

Using index map: Soil

Initial Moisture			
ID	1	2	3
Description1	Soil moisture...	Soil moisture...	Soil moisture...
Description2	
Initial moisture	0.150000	0.150000	0.150000





Turn on Green & Ampt Simulation

Watershed and Groundwater
Modeling Solutions

GSSHA Job Control Parameters

Computation parameters

Total time (min): 2000

Time step (sec): 10

Overland flow

Computation method: Explicit

☐ Interception

☐ Initial depth

☐ Retention depth

☐ Area reduction depth

Initialize GSSHA

Outlet information

Column: 1

Row: 64

Slope: 0.00100

Evapotranspiration

☒ No evaporation

☐ Deardorff method

☐ Penman method

☐ Seasonal resist.

Infiltration

☐ No infiltration

☐ Green + Ampt

☒ Green + Ampt with soil moisture redistribution

Delete GSSHA Data

Channel routing computation scheme

☐ No routing

☒ Diffusive wave

☐ MESH

Edit Parameters...


<input type="checkbox"/> Groundwater	Edit parameter...
<input type="checkbox"/> Soil erosion	Edit parameter...
<input type="checkbox"/> Long term simulation	Edit parameter...
<input type="checkbox"/> Contaminant transport	Edit parameter...
<input type="checkbox"/> Nutrients	Edit parameter...
<input type="checkbox"/> Storm/tile drain	Edit parameter...
<input type="checkbox"/> Stochastic	Edit parameter...
<input type="checkbox"/> Link CE-QUAL-W2 ...	Edit parameter...
<input type="checkbox"/> Manage files	Edit parameter...

Help **Output Control...** **OK** **Cancel**



Save and Run


Watershed and Groundwater
Modeling Solutions





Watershed and Groundwater
Modeling Solutions

Visualize the Infiltration Results





Watershed and Groundwater
Modeling Solutions

Workshop

